

POU Water Coolers

Sparta Series

A superb, space-saving POU cooler that will fit on almost any counter.



Models:

POU1CTHS (Hot N' Cold™)

POU1CTK (Cook N' Cold™)

- POU1CT does not include water treatment
- Stylish, contemporary, and sturdy design
- Large 2.5 gallon capacity stainless steel reservoir
- Heavy duty PVC cabinet available in white or black
- Dual float system with built-in safety float to prevent overflowing
- 1 piece hot tank
- Convenient handles on side panels enable easy transport and placement
- Easily removable drip receptor
- Available in Cook N' Cold™ and Hot N' Cold™
- 5 year limited warranty



Sparta Series Technical Data & Specifications



Dimensions:

W 12" x D 16.75" x H 17.5"

Net Weight (approx.):

Cook N'Cold™ - 44 lbs.

Hot N' Cold™ - 48 lbs.

Cabinet: Molded of heavy duty polyvinylchloride has UL94-5V rating. The soft off-white or black color is molded throughout to help conceal scratches from use

Cold Water Refrigeration Unit: Convection cooled condenser. Internally, spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat that is easily accessible.

Cold Water Reservoir: Type 300 series stainless steel. External copper refrigerant coil. Reservoir insulation is removable, molded, expanded bead polystyrene.

Float System: Dual mechanical floats include a safety lockout. Contains all non-metallic waterways. Float does not require electricity to operate

1 Piece Hot Water Tank: 500 watt heating element. One piece tank is easy to replace or service without breaking soldered refrigeration connections. The hot tank is type 300 series stainless steel.

Cold Water Capacity Table

Room Temp	Water Temp	Gallons per hour of 50°F Water	# of 3oz cups per hour
70°F	70°F	1.3	55
80°F	80°F	0.8	34
90°F	90°F	0.5	21
100°F	100°F	0.4	17

Hot Water Capacity: 45 x 6 oz cups of piping hot water per hour. 1 1/2 quart storage tank.

Hot Water Thermostat: Adjustable thermostat with safety limiter.

Hot Water Safer Faucet: Self closing faucet requires a two-step action that is easy for adults to use, but helps to protect small children. Faucets are made of durable polypropylene.

Drip Receptor: Drip tray lifts out for easy removal. Molded for durability, dishwasher safe.

Electrical: 115 volts, 60 Hertz. Water cooler compressor 1/20 hp. Three wire service cord and polarized plug furnished.

Warranty:(Within the Continental Limits of the United States and Canada) Limited five year warranty. 5 years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in this water cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.



Specifications are subject to change without notice.

©2009 OASIS International. OASIS® and the palm tree design are registered trademarks of OASIS International. Hot N' Cold™ and Cook N' Cold™ are trademarks of OASIS International.