

PureWaterCooler™

Lo-Profile Countertop Water Cooler

Hot and cold bottle-less cooler with built in filtration makes clean great tasting water. Sleek compact design fits under standard cabinets.

Features

- Two Temperature System
Cold: 37-50° F, Adjustable • Hot: 185° F, Autocontrol
- Built-In Reverse Osmosis Or Standard Filtration System.
- Single Dispensing Faucet With HOT And COLD Button Control.
- Dual Button Safety Feature For HOT.
- Low Height (Only 16 1/2") Fits Under Standard Cabinets.
- Solenoid Valve Inlet Water Control.
- Indicator Lights On Front Panel For Heating And Cooling.
- LED Indicator For Tank Full On Front Panel
- On/Off Switch In Rear To Control Heat And Cold Functions.

Special Features

- Built-In Moisture Sensor Shuts Off Water If Leak Occurs.
- Easy To Replace Disposable Twist-Off Filter Cartridge.
- High Efficiency Sealed Compressor.

Great for breakrooms, small offices and wet bars. At only 16.5" tall, this unit fits on counters under standard cabinets in homes and offices and can serve up to 30 people. Choose between Reverse Osmosis and Standard filtration for great tasting water where you need it. The filter cartridges are side panel accessible for easy replacement. The 2 temperature single dispensing faucet comes with a dual button Hot Water safety feature. The 8" tall opening allows easy refill of large water bottles and mugs. The built-in leak detector shuts off water if a leak occurs. In attractive silver and gray.



Side panel removes for easy access to filters

Specifications

Shipping Weight: 48 lb.
Dimension: 13"W x 14"D x 16.5"H
Cold tank volume 0.75 gal
Hot tank volume 1.0 Qt.
Cooling Rate: 1.5 gal/hr 37-50 °F
Heating Rate: 1.5 gal/hr 180 °F
Voltage: 115 VAC
Power Required: 600w max.

Filter System

Standard Filter **400F**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon

Reverse Osmosis Filter **400R**
Above 2 stages plus
Stage 3: 50-GPD RO Membrane

Fully assembled
- connection hardware included



Conforms to UL std 399

ADA Compliant

AVAILABLE OPTIONS

2-Temp Dispenser - 50 GPD Revers Osmosis

PWC-400R

2-Temp Dispenser - Standard Filtration

2-Temp Model W/ UV Sterilizer [\(more info\)](#)

See [PureWaterCooler Accessories](#)

Replacement Filters

Sediment

PWC-400F

add /UV

GAC Carbon

IFA-4035

IFA-4034

RO Membrane, 50GPD

MA-4203