

**PWC 7000**



**PureWaterCooler™**

## Largest Capacity Hot & Cold Cooler With 6.3 Gallon Storage

*Sleek, upscale bottle-less cooler with filtration provides great tasting hot and cold water from your tap. Contemporary styling fits with today's modern offices. Eliminates the hassle of 5-gallon bottles.*

### Features

- Two Temperature System  
Cold: 37-50° F, Adjustable • Hot: 185° F, Autocontrol  
LED Indicator For Hot Or Cold Water On The Front Panel
- 6.3 Gal Total Water Storage
- Built-In Filtration System Is Easily Accessed For Replacement  
Available With Reverse Osmosis Filtration System  
Or Standard Dual-Cartridge Filtration System
- Individual Cold And Hot On/Off Switches On Rear Panel
- Sealed Stainless Steel Cold Reservoir And Hot Tank
- Convenient, Recessed, No-Drip Dispensing Faucets
- High Efficiency Sealed Compressor Cooling System
- Taller 8" Fill Opening Allows Easy Access For Refills
- Available With Ultraviolet Or Ozone Sterilizer
- 1 Year Limited Warranty - 3 Year Compressor Warranty

All water-bearing materials in this water cooler comply with the Safe Water Drinking Act amendment of 1996, and are in compliance with NSF standard 61, section 9.



Conforms to UL std 399

**ADA Compliant**

This hot and cold bottle-less water cooler has 4 times the storage capacity of our other 2-temp models - **6.3 gallons**. Serves busy offices with up to 70 people. The taller 8" opening allows larger mugs and bottles easy access for refills. RO version comes with 100 GPD RO membrane. Choose models with Reverse Osmosis filtration for crystal clear water and the removal of minerals that cause scale deposits in coffeemakers and other fixtures. Use the Standard Filtration version for areas with softer water (under 5 grains of hardness), for fresh tasting water.

### Specifications

Shipping Weight: 80 lb.  
Dimension: 17"W x 17"D x 47"H  
Main tank volume 4.4gal  
Cold tank volume 1.1 gal  
Hot tank volume .8 gal  
Cooling Rate: 1.5 gal/hr 37-50 °F  
Heating Rate: 1.5 gal/hr 180 °F  
Voltage: 115 VAC  
Power Required: 600w max

### Filter System

Standard Filter **7000F**  
**Stage 1:** 5 micron Sediment  
**Stage 2:** 10 micron Activated Carbon  
  
Reverse Osmosis Filter **7000R**  
Above 2 stages plus  
**Stage 3:** 100-GPD RO Membrane  
  
Fully assembled  
- connection hardware included

**AVAILABLE OPTIONS**

<b>2-Temp Model - 100 GPD Reverse Osmosis</b>		<b>PWC-7000R</b>
<b>2-Temp Model - Standard Filtration</b>		<b>PWC-7000F</b>
<b>2-Temp Model W/ UV Sterilizer</b> <a href="#">(more info)</a>		<b>Add /UV</b>
<b>2-Temp Model W/ Ozone Sanitizer</b> <a href="#">(more info)</a>		<b>Add /OZ</b>
<b>Leak Detector Option</b> <a href="#">(more info)</a>		<b>LC-8021</b>
See <a href="#">PureWaterCooler Accessories</a>		
<b>Replacement Filters</b>	<b>Sediment</b>	<b>IFA-4035</b>
	<b>GAC Carbon</b>	<b>IFA-4034</b>
	<b>RO Membrane, 50 GPD</b>	<b>MA-4203</b>